



2 years hardware warranty. Extend it up to 5 years!



## Arteco 7000

Robustness and Powerful: Arteco 7000.

Arteco 7000 is the 19" rack mountable industrial surveillance server ideal for those who need to manage IP video surveillance designed for medium to large installations that require high performance and reliability. Arteco 7000 can handle IP video sources from all major international manufacturers and is compatible with ONVIF™ and RTSP devices. Not just a NVR, SEEtheDIFFERENCE, with this powerful system.

### **NVR EXPANDABLE UP TO 72 CHANNELS VIDEO IP**

Each Arteco 7000 comes pre-loaded and tested with your selection of Camera licenses (sold separately). Choose the version that fits your needs between Pure, eMotion, Active or Extreme, from 1 to 72\* camera licenses and we will prepare the ready-to-use NVR.

Do you require a flexible, robust system with ample recordings storage? The answer is Arteco 7000, a powerful NVR that offers the ability to install up to 8 HDD. Not sure if you will need to add storage in the future? Arteco 7000 gives you the ability to add storage capacity after installation thanks to disk controllers with full hot swap support.

### **OPTIONS AND UPGRADES**

Integrate your alarm and security systems using the Arteco CONTACT ID module for comprehensive control of your security. Complete your Arteco 7000 with the optional Arteco Everywhere I/O modules for a fully integrated security solution. Experience a system that maximizes your protection while minimizing unnecessary energy costs.

\* Number of cameras managed by a video surveillance server varies based on the Resolution of the Cameras used. Arteco 7000 maximum camera recommendation is based off field tests with D1 Resolution cameras.

Arteco certified hardware to match the software of your choice

Pure



eMotion



Active



Extreme



### Hardware Specs

- HDD 2TB (Expandable up to 24TB)
- 4x USB 2.0, 4x USB 3.0,
- 1 HDMI, 1 DVI-I, 1 Display Port
- 1x eSATA3 Port
- 2x Gigabit LAN
- 1x Ps/2 (k+m)
- 1 audio output jack 2.5 mm
- 1 Microphone input 2.5 mm
- 220/110 Vac, 50Hz, curr. 120 W
- Operating temperature 0 to 40 ° C, 80% RH max n
- Dimensions in mm: L430 x H132,5 x W445
- Installation kit for 19" Rack

### Choose the software to match your Arteco 7000

● standard   ○ optional   - not available		Pure	eMotion	Active	Extreme
<b>SERVER FEATURES</b>	Number of supported cameras per server	20	unlimited	unlimited	unlimited
	Number of supported servers	1	1	unlimited	unlimited
	Number of Simultaneous Connections	5	unlimited	unlimited	unlimited
	Number of users	unlimited	unlimited	unlimited	unlimited
	Support for Arteco Web Client	●	●	●	●
	Support for Arteco Mobile Next	●	●	●	●
	PTZ Control	●	●	●	●
	Dual Stream (Live and recording) per Camera	●	●	●	●
	Event Notification	●	●	●	●
	Multi Camera Playback	●	●	●	●
	Instant Replay	●	●	●	●
	Event search	●	●	●	●
	PTZ Presets &Tour	●	●	●	●
	Support Interconnection	-	●	●	●
	Multiple Stream Support	-	●	●	●
	Record to network storage	-	●	●	●
	Centralization	-	○	●	●
	Privacy Blur	-	○	●	●
	Camera Selections	-	○	●	●
	User policies definitions	-	○	●	●
Maps Supervisor	-	○	●	●	
Virtual I/O	-	○	●	●	
Virtual Machine	-	○	○	●	
Storage Failover	-	-	○	●	
Microsoft Active Directory support	-	-	○	●	
Server Hot backup	-	-	-	●	
<b>ANALYTICS</b>	Motion Detection Pure	●	●	●	●
	Analytics eMotion	-	●	●	●
	Analytics Active (Violated Area, Loitering, Virtual Trip-wire)	-	-	●	●
	Analytics Extreme (Violated Area, Loitering, Virtual Trip-wire, Abandoned/Removed, Counting, Speedthreshold)	-	-	-	●
<b>PLUGIN</b>	Arteco Everywhere Integration	●	●	●	●
	Intrusion System Generic Contact ID Plugin	-	○	○	○
	CIAS Extreme Perimeter Device plugin	-	○	○	○
	License Plate Recognition (LPR) plugin	-	○	○	○

[www.arteco-global.com/support](http://www.arteco-global.com/support)

- Arteco Academy
- License Management
- Hardware Calculator
- Supported Devices
- Download Area
- How To Videos
- Contact Support